


C Channels



DWG No.	A(mm)	B(mm)	T(mm)	W.T. (kg/m)	Remarks
C001	14	16	2.2±0.15	0,258	
C003	14	18	2.2±0.15	0,281	
1501-07	16	21	3.0±0.15	0,455	
C00002	25,6	25,6	不规则	0,411	
C00005	29,7	15	1,0	0,173	
☆C00021	39,37	15,88	1,52	0,314	外4-R0.38,内带V槽
NA-19	42	20	3.2±0.15	0,791	
YKD-04	47,5	24±0.36	1.5±0.15	0,464	内4-R1.0
C00018	50	25	1.4±0.15	0,399	
76B14S	76	20	1.2 ^{+0.05/-0.1}	0,391	B侧带装饰线
MOB-01A			0,9	0,347	
MOB-01B	76	25	1.1 ^{+0.05/-0.1}	0,422	
MOB-01C			1.4±0.15	0,533	
C00004	76	44	1.2±0.15	0,684	
LG202	80	20	2.0±0.15	0,649	内带V槽
XL-617	80	70	1.5±0.15	0,943	
XL-616	80	133	1.5±0.15	1,702	要撕筋
C00017	100	35	2,0	1,041	

注：*为有更改的型号，☆为新增型号(2007-08-22)。

无模具